

Guarantee:

Opticron SDL Eyepieces are of a very high quality both in their performance and construction. We guarantee some parts in these instruments for up to 10 years under the following conditions:

- (i) In the case of defects attributable to faulty processing or materials, we will assume responsibility for the labour and material costs during the first 5 years after purchase. We reserve the right to decide whether defective parts should be repaired or replaced.
- (ii) During the next 5 years we will assume responsibility for material costs only, charging corresponding labour costs.
- (iii) We will accept no liability for damage caused by incorrect use, water penetration - unless the eyepiece is properly connected to a waterproof telescope body, or for any repairs or actions which have been carried out outside our firm.
- (iv) Parts such as rubber eyecups and rubberised coatings etc. are excluded from the guarantee.

This guarantee is in addition and does not affect your statutory rights.

For more information please contact:

opticron

PO Box 370, Unit 21, Titan Court, Laporte Way, Luton,
Bedfordshire, LU4 8YR UK

Telephone: 01582 726522 Facsimile: 01582 723559

Email: sales@opticron.co.uk

© OPTICRON 2010

opticron



40935 SDL Eyepiece
User Guide and Guarantee

Specifications:

Eyerelief: 27-22mm Eyelens dia 26mm

Length: 68mm Weight: 246g

Eyepiece compatibility

Code	Magnification
40935	18-54x (HR 60/66) / 24-72x (HR 80)
40935E	20-60x (ES 80) / 27-80x (ES 100)
40935G	12-36x (GS 52) / 16-48x (GS 665) / 20-60x (GS 815)
40935I	16-48x (IMAGIC 65) / 20-60x (IMAGIC 80)
40935M	12-36x (MM2 52) Eyepiece adapter 40934 required
40935S	12-36x (IS 50) / 15-45x (IS 60) / 16-48x (IS 70) Eyepiece adapter 40927s required

Please note: 40935 does not connect to HR60 pre 1998,
Piccolo 60, Classic MKII, IF-2 MT/MTN telescopes

Care and cleaning

Opticron eyepieces require little maintenance but occasionally the outside surface of the eyelens will need cleaning. To avoid damaging this surface please read the following carefully.

- (i) Gently remove excess dirt and dust using a compressed air device or blower brush.
Caution: Hard and persistent rubbing of dirty surfaces can cause abrasive scratches on the surface of the glass which may distort viewing.
- (ii) Breathe on exposed glass surface and then wipe with an optical cleaning cloth (code 30277) in a circular motion until the surface is clean again.

Do not attempt to dismantle the eyepiece as this will invalidate the guarantee.